

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : <b>B60K 26/02, G05G 1/14</b>	<b>A1</b>	(11) International Publication Number: <b>WO 97/30863</b> (43) International Publication Date: 28 August 1997 (28.08.97)
<p>(21) International Application Number: PCT/GB97/00525</p> <p>(22) International Filing Date: 25 February 1997 (25.02.97)</p> <p>(30) Priority Data: 9604039.9                      26 February 1996 (26.02.96)                      GB</p> <p>(71) Applicant (for all designated States except US): ADWEST REARSBY LIMITED [GB/GB]; Gaddesby Lane, Rearsby, Leicester LE7 8TH (GB).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): THOMAS, Spencer, Peter [GB/GB]; 65 Fulford Road, Kirby Frith, Leicester LE3 6UL (GB).</p> <p>(74) Agent: SERJEANTS; 25 The Crescent, King Street, Leicester LE1 6RX (GB).</p>	<p>(81) Designated States: JP, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p><b>Published</b> With international search report.</p>	

(54) Title: DAMPED PEDAL MOUNTING

## (57) Abstract

A hysteresis-inducing pedal mounting for an accelerator pedal of a motor vehicle permits the hysteresis characteristic to be readily varied to meet the design parameters of the automobile in which it is to be fitted. The unit comprises a housing (11) for attachment to the accelerator pedal mounting (2) of the motor vehicle, with a lever arm (12) mounted in the housing to be movable as one with the accelerator pedal (1) over a permitted arc of pedal movement. A first friction member (16) fast to the housing (11) presents an inwardly facing curved reaction face, facing the lever arm (12) over the permitted arc of movement. A second friction member (15c) is biased radially outwardly from an end of the lever arm (12) into frictional contact with the reaction face of the first friction member (16) to create a frictional resistance to movement of the accelerator pedal (1).



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

-1-

TITLE

Damped Pedal Mounting

DESCRIPTIONField of the Invention

The invention relates to pedal mountings for the accelerator pedals of automobiles and provides a hysteresis-inducing unit for an accelerator pedal mounting which creates a desirable damped movement in use.

Background Art

Traditionally, the engine speed of an automobile has been controlled from a foot pedal, or accelerator pedal, via a rod or cable linkage to a carburettor or fuel injection system. Depression of the accelerator pedal causes an increase in the fuel supply to the engine, which thus increases speed. The rod or cable linkage has a frictional resistance to movement, which not only gives the accelerator pedal a familiar and recognizable 'feel' to the driver, but also reduces excessive oscillatory pedal movement or dither as a consequence of feedback from road shocks experienced by the moving vehicle.

A relatively recent development in automobile engine control is the introduction of the so-called 'drive-by-wire' system of engine control, in which a transducer is attached to the accelerator pedal, and the pedal position is translated by the transducer into an electrical signal which is delivered to the engine management system to control the vehicle engine speed. The electrical signal can be processed by the engine management system in order to provide the desired engine response, and it has been proposed that undue oscillatory movement of the pedal could be filtered out of the electrical signal at the engine management system. That represents an electronics-based solution to the problem of pedal dither.

-2-

Electrical processing of the accelerator pedal position signal does not, however, improve the 'feel' of an accelerator pedal which is linked to the engine and engine management system electrically rather than mechanically. Pedal mountings have therefore been proposed in which frictional forces resisting pedal movement, comparable to the frictional resistance of the traditional rod or cable linkage, are deliberately incorporated into the pedal mounting. Such mountings are designed to introduce hysteresis into the pedal movement, with a significantly larger force being required to initiate pedal movement than to maintain a constant pedal position.

One prior proposed hysteresis-inducing pedal mounting incorporates two coaxial friction discs, one associated with the pedal and the other associated with a housing for the pedal mounting. The discs are biased axially into frictional contact with each other, so as to provide a constant frictional resistance to pedal movement.

Another prior proposed hysteresis-inducing pedal mounting incorporates arcuate brake shoes spring-biased onto a pivot shaft for the accelerator pedal or onto an enlarged portion of that shaft.

An inherent characteristic of all prior proposed hysteresis-inducing pedal mountings is that the induced hysteresis, or frictional resistance to pedal movement, is constant over the entire range of pedal movement. Furthermore the two examples quoted above introduce frictional forces close to the pivotal axis of the pedal, so that in order to create a significant resistance to pedal movement the spring forces must be very substantial.

It is an object of the invention to provide a hysteresis-inducing pedal mounting which permits the hysteresis characteristic to be readily varied to meet the design parameters of the automobile in which it is to be

-3-

fitted, and which permits lighter springs to be used than in prior proposed mountings, while maintaining the unit of a size that can be fitted in the driver's footwell of a motor vehicle in the relatively limited space available.

It is a further object of the invention to provide a hysteresis-inducing unit that can be attached to an accelerator pedal mounting to impart a damped hysteresis characteristic and 'feel' to the accelerator pedal when that pedal is used in a 'drive-by-wire' engine control system.

#### The Invention

The invention provides a hysteresis-inducing unit for an accelerator pedal mounting of a motor vehicle, comprising: a housing for attachment to the accelerator pedal mounting, a lever arm mounted in the housing to be movable as one with the accelerator pedal over a permitted arc of pedal movement, a first friction member fast to the housing and presenting an inwardly facing curved reaction face, facing the lever arm over the permitted arc of movement of the lever arm, and a second friction member biased radially outwardly from an end of the lever arm into frictional contact with the reaction face, to create a frictional resistance to movement of the accelerator pedal.

The inwardly facing curved reaction face of the first friction member may be arcuate, with the centre of arc being the pivotal axis of the accelerator pedal and lever arm. That creates a uniform hysteresis characteristic over the range of pedal movement. Alternatively the reaction face may be of a curved shape which has a different radial spacing from the pedal pivotal axis for different pedal angles, so as to provide a non-uniform hysteresis characteristic over the range of pedal movement. For example, the reaction face may be closer to the pedal axis at one end, corresponding to maximum pedal

-4-

depression, than at the other, corresponding to minimum pedal depression. Moreover the spacing from the axis may vary uniformly or non-uniformly over the angular extent of the reaction face. The consequence of such a design of reaction face would be that the second friction member would be more strongly biased into frictional contact with the reaction surface for maximum pedal depression than for minimum pedal depression. The damping effect of the unit on pedal movement would therefore be greater for higher engine speeds than for lower engine speeds. No other hysteresis-inducing unit provides, at low cost, such a total control over the applied hysteresis characteristic imposed by the unit.

The second frictional member may be a member longitudinally movable relative to the lever arm and spring-biased radially outwardly from the distal end of the lever arm. The spring bias may be by a coil or leaf spring or other resilient means. A preferred and highly cost-effective second frictional member is, however, a steel leaf spring mounted at its ends on the distal end of the lever arm and resiliently presenting a portion intermediate its ends into direct frictional engagement with the reaction face of the first frictional member.

The frictional characteristics of the first and second friction members should be such as to provide a resistance to relative movement but not to prevent relative movement. High friction facings are not therefore necessary. Preferably the first friction member is made as an injection moulding from an acetal resin, such as that commercially available under the Trade Mark DELRIN, which has good wear resistance and is self-lubricating so as to give a very constant and reproducible frictional characteristic.

The length of the lever arm, the bias force on the second friction member and the frictional characteristics of the



-5-

first and second friction members together dictate the degree of damping which the unit creates. The unit may be mounted with the lever arm extending generally upwardly from the pivotal axis of the accelerator pedal, so as to extend into a void space which is generally available, or which can be made available by design, on a motor vehicle. The availability of this void space means that the length of the lever arm can be extended to allow for the use of correspondingly reduced spring bias pressures between the friction members.

Generally speaking a position transducer for the accelerator pedal, such as a potentiometer, is mounted coaxially with the pivotal axis of the accelerator pedal on one side of the pedal, and the unit according to the invention can be mounted on the opposite side of the pedal.

#### Drawings

Figure 1 is a perspective view of an accelerator pedal of a motor vehicle, with a hysteresis-inducing unit according to the invention mounted thereto;

Figure 2 is a front elevation of the pedal mounting of Figure 1, showing a pedal position-responsive transducer on one side and the unit according to the invention on the other side of the pedal; and

Figure 3 is a transverse section through the hysteresis-inducing unit of Figures 1 and 2.

In Figure 1, one wall of the hysteresis-inducing unit of the invention has been shown cut away so as to expose the lever arm within the unit for the purpose of illustration only.

Figure 1 shows an accelerator pedal 1 pivotally supported by a mounting 2. At a lower end of pedal 1 is a foot-engageable pad 3, depression of which causes the pedal 1 to move pivotally about a pivot axis 4. On the

-6-

opposite side of the pivot axis 4 to the foot pad 3, the pedal has an integral lever arm 5 which receives one end of a return spring 6 the opposite end of which is anchored to a reaction member, not shown, fast to the vehicle body.

The pedal 1 illustrated in Figure 1 is a universal design which can be used with a cable transmission to the engine speed control mechanism or with an electrical transmission. If a cable transmission were used, then one end of the transmission cable would be anchored in a receiving recess 7 at the top of the lever arm 5. As illustrated, however, the pedal 1 is provided with an electrical transmission link. A potentiometer 8 is mounted on one side of the pedal 1 (the left hand side as seen from the driver's position) co-axial with the pivotal axis 4. The electrical output of the potentiometer 8 is a direct measure of the pedal position, and is transmitted by wire (not shown) to the engine management system of the vehicle.

In order to provide the pedal 1 with the appropriate 'feel' to the driver, even in the absence of a cable link to the engine compartment of the vehicle, there is provided a hystereis-inducing unit 10 according to the invention, mounted coaxially with the pivot axis 4 on the opposite side of the foot pedal 1 to the potentiometer 8 (see particularly Figure 2).

The unit 10 comprises a housing 11 fast to the mounting 2. Within the housing 11 is a lever arm 12 secured to a pivot shaft 13 of the accelerator pedal 1 and movable as one with the accelerator pedal 1. Figure 3 most clearly illustrates the shape and disposition of the lever arm 12. At its distal end 14 it carries a leaf spring 15 made from spring steel. The two opposite ends 15a, 15b of the leaf spring 15 bear on the lever arm 12 and an intermediate portion 15c is resiliently biased against a curved inwardly facing surface of a friction pad 16. The

**SUBSTITUTE SHEET (RULE 26)**

-7-

friction pad 16 forms a first friction member of the hysteresis-inducing unit 10 and the intermediate portion 15c of the leaf spring 15 forms a second friction member. Pedal movement causes the second member 15c to slide over the first, with a frictional resistance to movement, thus simulating the frictional resistance to movement of a conventional cable transmission to the engine compartment.

Accurate control of the hysteresis effect induced by the unit 10 is possible because the lever arm 12 can be made of a length sufficient to create a desirable damping effect even when using a relatively light spring 15. The surface of the spring 15 is smooth, so that it can slide over the internally facing curved face of the friction pad 16 with a smooth frictional drag. The smoothness of movement may be enhanced by making the friction pad 16 of a smooth surfaced self-lubricating material such as DELRIN (Trade Mark) polyacetal.

The internally facing curved face of the friction pad 16 may be arcuate, centred around the axis 4, in which case the preloading force of the spring 15 is constant for all degrees of angular movement of the pedal 1. That gives a hysteresis characteristic or pedal damping effect which is uniform over the whole range of pedal movement. That may be desirable in some installations. In other vehicle designs, however, it may be desirable to have the hysteresis characteristic vary with progressive pedal movement. For example, a greater drag factor on pedal movement may be desirable for higher vehicle speeds (and therefore engine speeds) than for lower. That can readily be accommodated by the unit 10, by shaping the internally facing curved face of the friction pad 16 so that it is non-arcuate, or arcuate but not centred around the axis 4, so that at maximum pedal movement the spring 15 is more highly compressed than at minimum pedal movement.

-8-

It is a significant advantage of the unit according to the invention that the hysteresis characteristic imparted to the pedal can be changed simply by changing the shape of the friction pad 16. The pad 16 is therefore designed as a simple clip-on component to an otherwise standardized design of housing 11. Differently shaped pads 16 can be provided for different motor vehicles.

Another significant advantage of the unit according to the invention is that it does not protrude significantly below the pivotal axis 4. Instead, the lever arm 5 extends above the axis 4 so that the unit is positioned substantially wholly in the void space above the pedal mounting 2, where conventionally such void space is available and where the unit does not interfere with the driver's foot movement.

CLAIMS

1. A hysteresis-inducing unit for an accelerator pedal (1) mounted on an accelerator pedal mounting (2) of a motor vehicle, comprising:

a housing (11) for attachment to the accelerator pedal mounting (2);

a lever arm (12) mounted in the housing (11) to be movable as one with the accelerator pedal (1) over a permitted arc of pedal movement;

a first friction member (16) fast to the housing (11), and presenting an inwardly facing curved reaction face, facing the lever arm (12) over the permitted arc of movement of the lever arm (12); and

a second friction member (15c) biased radially outwardly from an end of the lever arm (12) into frictional contact with the reaction face, to create a frictional resistance to movement of the accelerator pedal (1).

2. A unit according to claim 1, wherein the inwardly facing curved reaction face of the first friction member (16) is arcuate, with the centre of arc being the pivotal axis (4) of the accelerator pedal (1) and lever arm (12).

3. A unit according to claim 1, wherein the inwardly facing curved reaction face of the first friction member (16) is of a curved shape which has a different radial spacing from the pivotal axis (4) of the accelerator pedal (1) and lever arm (12) for different pedal angles, so as to provide a non-uniform hysteresis characteristic over the range of pedal movement.

4. A unit according to claim 3, wherein the reaction face is closer to the pedal axis (4) at the end corresponding to maximum pedal depression than at the other end, corresponding to minimum pedal depression.

-10-

5. A unit according to claim 2, wherein the second frictional member (15c) is a member longitudinally movable relative to the lever arm (12) and spring-biassed radially outwardly from the distal end of the lever arm (12).


6. A unit according to claim 5, wherein the means biassing the second friction member (15c) into frictional contact with the reaction face is a coil or leaf spring.

7. A unit according to claim 6, wherein the means providing the spring bias is a steel-leaf spring (15) mounted at its ends on the distal end of the lever arm (12) and resiliently presenting a portion (15c) intermediate its ends (15a,15b) into direct frictional engagement with the reaction face of the first friction member (16).

8. A unit according to claim 3, wherein the second frictional member (15c) is a member longitudinally movable relative to the lever arm (12) and spring-biassed radially outwardly from the distal end of the lever arm (12).

9. A unit according to claim 8, wherein the means biassing the second friction member (15c) into frictional contact with the reaction face is a coil or leaf spring.


10. A unit according to claim 9, wherein the means providing the spring bias is a steel-leaf spring (15) mounted at its ends on the distal end of the lever arm (12) and resiliently presenting a portion (15c) intermediate its ends (15a,15b) into direct frictional engagement with the reaction face of the first friction member (16).



SUBSTITUTE SHEET (RULE 26)

2/3

FIG.2




SUBSTITUTE SHEET (RULE 26)




2/3

FIG.2



SUBSTITUTE SHEET (RULE 26)






FIG.3

# INTERNATIONAL SEARCH REPORT

Inter. Application No.  
PCT/GB 97/00525

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 B60K26/02 G05G1/14

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 B60K G05G F02D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y	DE 44 07 005 C (HELLA KG) 9 March 1995 see column 3, line 29 - column 4, line 16 see figure 1	1 3,4
Y	DE 43 00 096 A (VDO ADOLF SCHINDLING) 7 July 1994	3,4
A	see column 3, paragraph 3 see figure 1	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \*&\* document member of the same patent family

Date of the actual completion of the international search

2 June 1997

Date of mailing of the international search report

09 -06- 1997

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+ 31-70) 340-3016

Authorized officer

Clasen, M

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 97/00525

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 4407005 C	09-03-95	EP 0670235 A	06-09-95
DE 4300096 A	07-07-94	NONE	

**THIS PAGE BLANK (USPTO)**